

"Precision instruments, Intelligent Solution"

Applications:

Make- SFIC

Model-SFIC-EMF-MAG-MS110
MOC- MS Input 24VDC/
220VAC, Battery Output
4-20mA/RS485/Pulse, Hart,
GPRS Linner Rubber/PTFE
Connection Flange/
Tri-clamp/Thread/Clamp
Pressure PN16 Protection
Class IP65 Accuracy 0.5%
Electrode 3161/fltanium/Hc/
Tantalum Size DN15-DN2000
Application conductive liquid
(waste water, water...)

Our Client

















Sailent Features





stability & reliability





electronics







ased on Faraday's law of

on hermetically sealed welded construction





"Precision instruments, Intelligent Solution"

Applications:

Make- SFIC Model-SFIC-EMF-MAG-110 Input 24VDC/220VAC, Battery Output 4-20mA/RS485/Pulse, Hart Cable 5M*2 cable Connection Insertion Protection Class IP65/IP68 Sensor material PTFE/Rubber Accuracy 1.0% Electrode 316L/titanium/HC/Tantalum Size DN300-DN2000 Application conductive I

iquid(waste water,water...)





















Sailent Features

















"Precision instruments, Intelligent Solution"

Applications:

Make- SFIC Model-SFIC-EMF-MAG-INS110 Input 24VDC/220VAC, Battery Output 4-20mA/RS485/Pulse, Hart Cable 5M*2 cable Connection Insertion Protection Class IP65/IP68 Sensor material PTFE/Rubber Accuracy 1.0% Electrode 316L/titanium/HC/Tantalum Size DN300-DN2000

Application conductive I iquid(waste water,water...)

Our Client

















Sailent Features





















"Precision instruments, Intelligent Solution"

Applications:

Make- SFIC Model-SFIC-VFM-SS110 Material SS316 Input 24VDC, Battery Output 4-20mA/ RS485 Temp Below 250 degrees Feature Temperature pressure compensation Connection Sandwich Type Pressure PN16 Accuracy 1.0% Protection Class IP65/IP68 Size DN15-DN1000 Application Steam, compressed air.hot water...



















Sailent Features















+91 8237013503 | +91 8530567503



"Precision instruments, Intelligent Solution"

Applications:

Make - SEIC

Model- SFIC-TFM-110

Media: Liquids (Clear)

Viscosity: 100 cp max Line Size: 15 NB to 150 Nb

Display: 16x2 LCD-4 digit

Transmitter Electronics:

option 1: Integral : option 2: Remote Remote Electronics Cable: 25 mtr max

Type of Output: 1) 4-20 mA DC

Pulse-30mA Peak-Peak

Linearity: ±1%

Repeatability: ±1%

Turn down ration: 10:1 or 100:1

Process Temperature: 0-85Deg. C max

Process Pressure: 0-20 kg/cm2 max

Power Supply: 24V DC

Power Consumption: < 0.5 VA

Response Time: <100mSec

. Mounting : In-line (Horizontal or Vertical)

Our Client





















Sailent Features















electromagnetic induction hermetically sealed





+91 8237013503 | +91 8530567503



"Precision instruments, Intelligent Solution"

Applications:

Product- Coriolis mass flow meter Material SS316 Input 220VAC,24VDC Output 4-20mA/RS485, Pulse,Hart Connection Flange/Threaded/Clamp Pressure PN16 Size DN15-DN200 Application molasses,measure gas, liquid,etc.

Our Client

















Sailent Features

















ased on Faraday's law of 6 ectromagnetic induction he

(a) aglas agait





"Precision instruments, Intelligent Solution"

Applications:

Make- SFIC

Model-SFIC-EMF-MAG-SS110(SW)

MOC-SS304/SS316/SS316L

Input 24VDC/220VAC

Output- 4-20mA/RS485/ Pulse.Hart.GPRS

Linner- Rubber/PTFE

Connection- FLANGED,

Pressure- PN16
Protection Class IP65

Accuracy- 0.5%

Electrode -316L/titanium/

HC/Tantalum

Size DN15-DN200 Applicationconductive liquid (Milk, juices,

pulp,etc.)

Our Client





















Sailent Features











electronics





lased on Faraday's law of

welded construction



+91 8237013503 | +91 8530567503



"Precision instruments, Intelligent Solution"

Applications:

Make-SFIC Model- SFIC-CLP-UF-110 MOC-Plastic, Input 220VAC, 24VDC Output 4-20mA/ RS485 Size DN15- DN6000 Probe S M L Temprange-20-90°C/-20-160°C Application measuring liquid in the pipe

Our Client



















Sailent Features




















sales@saitechflowinstru.com www.saitechflowinstru.com



+91 8237013503 | +91 8530567503



"Precision instruments, Intelligent Solution"

Applications:

Model-Woltman Water Meter Product standard ISO 4064:1993 class B

Water Temp. 50 to 90 deg.celcius Water Pressure < 1.6MPa

Other features: Magnetic drive ,Lower transmission resistance, low pressure loss, long working life not affected by external

magnetic field register may be rotated through 360 degree dry dial register

ensures clear readina.

Our Client





















Sailent Features



















+91 8237013503 | +91 8530567503



"Precision instruments, Intelligent Solution"



Applications:

Casing material Plastic Polymer Dimensions (W x H x D) 100mm x 93mm x 28 mm (LXWXH) Weight 160 grams

Mounting options Wall Mount, Flat surface, Bottom DIN rail

Our Client



















Sailent Features















electromagnetic induction hermetically sealed





"Precision instruments, Intelligent Solution"

Applications:

Multijet Water Flow Meter. Line Size 15mm-50mm Model No.: Multijet water meter End Connection:-THREADED TYPE Product Standard ISO-4064 Body brass Temperature-less 50 deg C

Dial Registration- 99999KL

Our Client





















Sailent Features























+91 8237013503 | +91 8530567503



"Precision instruments, Intelligent Solution"

Applications:

- M Product- TRI CLAMP FLOW METER
- r√ Make- SFIC
- MOC-SS304/SS316/SS316L Input 24VDC/ 220VAC Output- 4-20mA/RS485/Pulse,
- Hart.GPRS
- √ Linner- Rubber/PTFE Connection-Tri-clamp, Pressure- PN16
- Protection Class IP65 Accuracy- 0.5%
- F/ Electrode -316L/titanium/HC/Tantalum
- Size DN15-DN150 Application- conductive liquid(Milk,juices,pulp,etc.)

Our Client





















Sailent Features















+91 8237013503 | +91 8530567503



"Precision instruments, Intelligent Solution"

Applications:

- Make-SFIC
- Model-SFIC-EMF-MAG-SS110
- MOC-SS304/SS316/SS316L Input 24VDC/220VAC
- Output- 4-20mA/RS485/ Pulse,Hart,GPRS
- √ Linner- Rubber/PTFE
- Connection-FLANGED,
- Pressure- PN16
- ✓ Protection Class IP65 Accuracy- 0.5%
- ☑ Electrode -316L/titanium/HC/Tantalum
- ✓ Size DN15-DN200 Application- conductive
- ☑ liquid(Milk,juices,pulp,etc.)

Our Client























Sailent Features















electromagnetic induction hermetically sealed

